## WIOLA L35G50P Car transporter tilt-bed GVW 3500kg with alu panels on the floor



Product short description:

Internal dimension (cm): 500 x 206

Capacity: 2546 kg

DMC Min: 2700 kg

DMC Max: 3500 kg

## **Product description:**

Low loader tow truck - three axles with overrun brake. Tilt hydraulically.

The frame is made of Domex 420 steel up to 4mm thick.

Anti-corrosion coating - hot-dip galvanized with powder coated sides.

Up to 36 months warranty.

## **Standard equipment**

3 braked axles AL-KO 3x1250kg

Lifting device AL-KO 3500kg with AKS-system

Tires 195/55 R10C

Independent suspension on the torsion bar spring

V-drawbar

better AL-KO winch

Strong support wheel

AL-KO AKS 3004 stablizing system

Supporting frames: structural steel with increased strength, welded construction

Transport surface: Aluminum panel 6mm with oval LOHR system holes, small aluminum ramp 300mm

Powder-coated side panels - on request possible to order with different color (black, blue, red, orange)

Corrosion protection: hot dip galvanized construction

Hydraulic tilting device

double-acting hydraulic cylinder for lifting and lowering

Wheels 2 pieces

Spare wheel

Information:

Added specification on the website came from producers and distributors pages, despite the effort while we add them, they could have some mistakes. Descriptions and photos are not basis for claims from our company. If you found some mistakes in our description, please let us know to e-mail address sklep@mazzo.pl